

TEKNOSPIR/4SP

EN 856 4SP

TUBI CON RINFORZO IN ACCIAIO SPIRALATO

WIRE SPIRALLED REINFORCED HOSES



4 spirali di acciaio ad alto carico
high tensile steel spirals

tubi con rinforzo in acciaio spiralato per linee di potenza con pressioni molto elevate

wire spiralled reinforced hoses for very high pressure power lines

TEMPERATURA DI ESERCIZIO:

- 40°C/+100°C
con punte di +125°C

FLUIDI DA UTILIZZARE:

oli minerali, oli vegetali e di colza, oli a base di glicoli e poliglicoli, oli a base di esteri sintetici, oli in emulsione acquosa, acqua

SOTTOSTRATO:

gomma sintetica resistente agli olii

RINFORZO:

quattro spirali di acciaio ad alto carico

COPERTURA:

gomma sintetica nera resistente agli oli ed alle condizioni ambientali

OPERATING TEMPERATURE RANGE:

- 40°C/+100°C
with peak of +125°C

QUALIFIED FLUIDS:

mineral oils, vegetable and rapeseed oils, glycol and polyglycol based oils, synthetic ester based oils, oils in aqueous emulsion, water

TUBE:

oil resistant synthetic rubber

REINFORCEMENT:

four high tensile steel spirals

COVER:

black, oil and environment resistant synthetic rubber

Code	 Hose size			 Reinforcement diameter		 Outside diameter		 Max working pressure		 Minimum burst pressure		 Minimum bend radius		 Weight	
	DN	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	lb/ft	Kg/mt
TS4SP04	6	1/4"	6,4	0,58	14,7	0,70	17,9	7250	500	29000	2000	5,91	150	0,40	0,600
TS4SP06	10	3/8"	9,5	0,69	17,5	0,84	21,4	6650	460	26600	1840	7,09	180	0,52	0,780
TS4SP08	12	1/2"	12,8	0,80	20,2	0,97	24,6	6150	425	24600	1700	9,06	230	0,62	0,920
TS4SP10	16	5/8"	16,0	0,94	23,8	1,11	28,2	5800	400	23200	1600	9,84	250	0,78	1,155
TS4SP12	19	3/4"	19,0	1,11	28,2	1,27	32,2	5500	380	22000	1520	11,81	300	1,02	1,520
TS4SP16	25	1"	25,4	1,39	35,3	1,54	39,0	4600	320	18400	1280	13,39	340	1,34	2,000
TS4SP20	31	1" 1/4	31,8	1,81	46,0	1,98	50,2	3000	210	12000	840	18,11	460	2,02	3,000
TS4SP24	38	1" 1/2	38,1	2,06	52,4	2,24	57,0	2650	185	10600	740	22,05	560	2,45	3,650
TS4SP32	51	2"	50,8	2,57	65,4	2,79	70,8	2550	175	10200	700	25,98	660	3,53	5,250